



### Adjustable Pole Stand

The APD-100 has two pole sections as well as a multi-angle display head adjustment, giving you the choice of three different display heights which gives you the flexibility to tailor the display position to your unique application.

### Displays up to 40 characters of alphanumeric text

Clear, easy-to-read 20-column x 2-line dot matrix, comma, decimal point, annunciator characters on a wide viewing display.

### Supports Multiple Command Modes

The Adesso APD-100 also offers a variety of command modes including Epson, Aedex, CD5220, etc...supporting multiple different modes.

### Multi-Language Support

Supports over 15 languages ranging from French, to German, to Italian, to Spanish and English. Use the APD-100 without language barriers or limitations.

### Vacuum Fluorescent Display


The APD-100 uses a Vacuum Fluorescent Display (VFD) tube which presents bright and easy to read characters. Because of the built-in VFD technology, the display is viewable from a wide angle.

### Multi-angled Display

The easy to read display also can be adjusted, and customized to your viewing preference for faster productivity. Adjust the display viewing angles up to 45°.



Displays up to 40 characters



Adjustable Pole Stand



Multi-Language Support



Vacuum Fluorescent Display

### Specifications:

Display Method:	Vacuum Fluorescent Display (Blue-Green)
Number of Characters:	40 (20 x 2 lines)
Brightness:	700 cd /m2
Character Font:	5x7 dot matrix
Character Type:	96 Alphanumeric, 13 International Characters
Character Size:	0.14" (3.5mm) x 0.20" (5.0mm)
Dot Size:	0.03" (0.75mm) x 0.03" (0.75mm)
Panel Dimensions:	8.0" (W) x 1.6"(L) x 2.6" (H) (203mm x 66 mm x 41mm)
Base Dimensions:	4.5" (W) x 7.25"(L) x 1.1" (H) (114mm x 185 mm x 28mm)
Pole Extender Dimensions:	6.0"(L) & 1.3"(Diameter). (18mm(L) & 33mm(Diameter)
Maximum Total Height:	7.25" to 16.625" (183mm to 423mm)
Viewing Angle:	Max 45°
Weight :	Approx. 0.9 kg (2lbs)
Command Modes:	ADM787, AEDEX, CD5220, DSP800, ESCPOS, ICD2002, NCR, PD6000, UTC_E, UTC_S
Language Support:	English (US & UK), French, German, Danish, Swedish, Italian, Spanish, Japanese, Norwegian, Bosnian, Croatian, Czech, Hungarian, Polish, Romanian, Czechoslovakian, Slovene, Slovenski, Portuguese, Arabic, Persian, Greek, Turkish, Estonian, Lithuania, Latvian, Bulgarian, Serbian, Macedonian & Mid-to-Eastern Europe Latin Languages.
Reliability (MTBF):	30,000 hours
Baud Rate :	Direct connection 9,600 or 19,200 bps
Power Consumption:	5 VDC @ 2.5W
Safety Certifications:	FCC; CE

### Requirements:

Operating System	Windows® XP / 7 / 8 / 10. OPOS Systems
Connectivity Interface	USB & Serial (RS-232)

### Includes:

- APD-100
- Quickstart Guide

### Shipping Information:

Item	UPC Code	Box Dimensions	Box Wt.	Qty/Ctn
APD-100	783750007627	10" x 8.5" x 4.5"	2 lbs	10

