



Adjustable Pole Stand

The APD-200 has two pole sections as well as a multi-angle display head adjustment, giving you the choice of three different display heights which gives you the flexibility to tailor the display position to your unique application.

Displays up to 40 characters of alphanumeric text

Clear, easy-to-read 20-column x 2-line dot matrix, comma, decimal point, annunciator characters on a wide viewing display.

Supports Multiple Command Modes

The Adesso APD-200 also offers a variety of emulation modes including Epson, Aedex, CD5220, etc...supporting multiple different modes.

Multi-Language Support

Supports over 15 languages ranging from French, to German, to Italian, to Spanish and Russian. Use the APD-200 without language barriers or limitations.

Vacuum Fluorescent Display

The APD-200 uses a Vacuum Fluorescent Display (VFD) tube which presents bright and easy to read characters. Because of the built-in VFD technology, the display is viewable from a wide angle.

Multi-angled Display

The easy to read display also can be adjusted, and customized to your viewing preference for faster productivity. Adjust the display viewing angles from up to 45° and horizontal rotation up to 360°.



Displays up to 40 characters



Adjustable Pole Stand



Multi-Language Support



Vacuum Fluorescent Display

Specifications:

Display Method:	Vacuum Fluorescent Display (Blue-Green)
Number of Characters:	40 (20 x 2 lines)
Brightness:	700 cd /m2
Character Font:	5x7 dot matrix
Character Type:	96 Alphanumeric, 13 International Characters
Character Size:	0.21" (5.25mm) x 0.35" (9.0mm)
Dot Size:	0.04" (1.1mm) x 0.05" (1.3mm)
Panel Dimensions:	8.8" (W) x 1.5"(L) x 3.5" (H) (225mm x 38 mm x 88mm)
Base Dimensions:	4.5" (W) x 7.25"(L) x 1.1" (H) (114mm x 185 mm x 28mm)
Pole Extender Dimensions:	6.0"(L) & 1.4"(Diameter). (154mm(L) & 35mm(Diameter)
Maximum Total Height:	8" to 18.5" (200mm to 467mm)
Viewing Angle:	Tilting up to 45°. 360° horizontal rotation
Weight :	Approx. 0.9 kg (2lbs)
Command Modes:	ADM787, AEDEX, CD5220, DSP800, ESCPOS, ICD2002, NCR, PD6000, UTC_E, UTC_S
Language Support:	English (US & UK), French, German, Danish, Swedish, Italian, Spanish, Japanese, Norwegian, Bosnian, Croatian, Czech, Hungarian, Polish, Romanian, Czechoslovakian, Slovene, Slovenski, Portuguese, Arabic, Persian, Greek, Turkish, Estonian, Lithuanian, Latvian, Bulgarian, Serbian, Macedonian & Mid-to-Eastern Europe Latin Languages.
Reliability (MTBF):	30,000 hours
Baud Rate :	Direct connection 9,600 or 19,200 bps
Power Consumption:	5 VDC @ 2.5W
Safety Certifications:	FCC; CE

Requirements:

Operating System	Windows® XP / 7 / 8 / 10. OPOS Systems
Connectivity Interface	USB & Serial (RS-232)

Includes:

- APD-200
- Quickstart Guide

Shipping Information:

Item	UPC Code	Box Dimensions	Box Wt.	Qty/Ctn
APD-200	783750008631	10" x 8.5" x 4.5"	2 lbs	10

